

Huskie SP-100

Hydraulic Operated Remote Cutting Head

www.spartacogroup.com

HuskieToolFacts

Specifications	
Weight	29 lbs.
Length	24"L
Jaw Opening	4″
Capacities	
Wire Ropes	Do Not Cut
Soft Steel Bolts	Do Not Cut
Rebar, Ground & Anchor Rods	Do Not Cut
Cu & Al Wire	3-1/2″
ACSR	Do Not Cut
Standard Guy Wire	Do Not Cut
Chain	Do Not Cut
Comm. Cables	4″
Lead Sheath Cables	4″



The **SP-SERIES** remote head units connect to any 10,000 psi, high pressure, hydraulic pumping system. Choose from ten different models of cutters, to cut costs and efforts. A 3/8" screw-type male coupler is supplied with each tool. Huskie Tools remote cutters have a hinged head which can be opened for easy cable or bar insertion. The movable blade advances in a shear fashion, to cut the material cleanly. When the cutting pressure is relieved an internal ram spring retracts the blade. The guillotine cutting style was chosen over scissor type cutting because of its powerful output force, larger cable capacities, compact size and reliability.

All tools can be used under water, consult factory for specific applications.

NOTE: FOR EHS GUY WIRE SPECIFY S-24CC, S-32CC OR THE REMOTE HEAD SP-24CC.

www.spartacogroup.com

800-860-6170