

## SP-24CC

### Hydraulic Operated Remote Cutting Head

#### Specifications

Output	7.8 Ton
Weight	21 lbs.
Length	14"
Jaw Opening	.9"

#### Capacities

Wire Ropes	Do Not Cut
Soft Steel Bolts	16mm, 5/8"
Rebar, Ground & Anchor Rod	16mm, 5/8"
Cu & Al Wire	Do Not Cut
ACSR	Do Not Cut
Standard Guy Wire	14mm, 9/16" EHS
Chain	1/4"
Comm. Cables	Do Not Cut
Lead Sheath Cables	Do Not Cut

#### Feature

- Lightweight and Portable
- Operate from Any 10,000 psi Hydraulic Source
- Works in Any Position



The **SP-SERIES** remote head units connect to any 10,000 psi, high pressure, hydraulic pumping system. Choose from seven different models of production cutters, to cut costs and efforts. A 3/8" screw-type male coupler is supplied with each tool. Huskie Tools remote cutters have a hinged head which can be opened for easy cable or bar insertion. The movable blade advances in a shear fashion, to cut the material cleanly. When the cutting pressure is relieved an internal ram spring retracts the blade. The guillotine cutting style was chosen over scissor type cutting because of its powerful output force, larger cable capacities, compact size and reliability.

All tools can be used under water, consult factory for specific applications.