## **8 TON INLINE HARD METAL CUTTING TOOL**

SL-RLS740L

75KV

ГОО

NAPPANT

180° HEAD TURN RADIUS

HUSKI **PROTIP** 

ALWAYS SECURE LATCH BEFORE OPERATING OR TOOL

DAMAGE WILL OCCUR

## **MATERIAL CUTTING APPLICATIONS**

WIRE Rope	REBAR (SC 40)	REBAR (SC 60)	GROUND ROD	ACSR	GUY WIRE	Cu/Al CABLE
3/4" DIA.	5/8" DIA.	5/8" DIA.	5/8" DIA.	1590 MCM	5/8" DIA.	1.5" DIA.

Powerful, large capacity head cuts up to 1590 ACSR and a wide variety of materials

## **FEATURES**

Latched cutting head for superior shear strength on tough materials

Head rotates 180° for optimum maneuverability in tight workspaces

5-year tool, 3-year battery Huskie Tools' limited warranty

75kV live line rated

## SPECIFICATIONS

CUTTING FORCE	8 Ton
WEIGHT	12.0 lbs (5.4 kg)
DIMENSIONS (H X L X W)	20.1" x 5.2" x 4.0", 12 x 13

CUTTING CAPACITIES			CUTTING ESTIMATES (5.0Ah BATTERY)		
WIRE ROPE	3/4" Dia.		797 ACSR	135 Cycles/Charge	
REBAR (SC 40)	5/8" Dia.		3/4" WIRE ROPE	95 Cycles/Charge	
REBAR (SC 60)	5/8" Dia.		5/8" REBAR	165 Cycles/Charge	
GROUND ROD	5/8" Dia.		5/8" GROUND ROD	165 Cycles/Charge	
ACSR	1590 MCM		3/8" GUY WIRE	200 Cycles/Charge	
GUY WIRE	5/8" Dia.				
CU/AL CABLE	1.5" Dia.				

PRODUCT NO.	KIT INCLUDES
SL-RLS740L-1	8 Ton Cutting Tool, (1) MILWAUKEE RED-LITHIUM™ 5.0Ah, 120VAC Charger, Tool Bag
SL-RLS740LDC-1	8 Ton Cutting Tool, (1) MILWAUKEE RED-LITHIUM™ 5.0Ah, 12VDC Charger, Tool Bag
SL-RLS740LX	8 Ton Cutting Tool, Bare Tool with Tool Bag

Huskie Tools is not affiliated with, authorized, or endorsed by Milwaukee Electric Tool Corporation. Milwaukee listed batteries and chargers are being re-sold by Huskie Tools. Milwaukee\* M18<sup>TM</sup> REDLITHIUM<sup>TM</sup> are registered trademarks of Milwaukee Electric Tool Corporation. Huskie Tools is not affiliated with, authorized, or endorsed by Makita\* Corporation. Makita\* listed batteries and chargers are being re-sold by Huskie Tools. Makita\* and LXT\* are registered trademarks of Makita\* Corporation.



LINEMAN PROVEN UTILITY APPROVED SINCE 1978

HUSKIETOOLS.COM









	8 Ton
	12.0 lbs (5.4 kg)
V)	20.1" x 5.2" x 4.0", 12 x 134 x 103 mm