SLA 6.6 TON INLINE LATCHED-HEAD CRIMPING TOOL

SLA-RL758U MILWAUKEE BATTERY POWER | SLA-MK758U MAKITA BATTERY POWER



CONNECTOR RANGE

LUGS & SPLICES

H-TAPS

Up to 4/O

NEW

AUTO-RETRACT WITH JOG & HOLD TRIGGER

Easy-to-use trigger provides optimal Crimping/crimping accuracy.

#8 to 500 MCM Cu

#8 to 350 MCM AI

25% FASTER

Improved hydraulics deliver faster Crimping/crimping speeds under load.

COMPACT, DURABLE & DEPENDABLE

Lighter weight with steel hydraulic body for longer life. Smaller and shorter for improved balance.

SPECIFICATIONS	
CRIMP FORCE	6.6 Ton
WEIGHT	5.35 lbs w/o battery
DIMENSIONS (H X L X W)	15.0" x 3.75" x 2.75"

CRIMPING ESTIMATES (5.0Ah BATTERY)	
4/0-4/0 H-TAP	200 Cycles/Charge
500 MCM CU	200 Cycles/Charge

CONNECTOR RANGE		
LUGS & SPLICES	#8 to 500 MCM Cu, #8 to 350 MCM AI	
H-TAPS	Up to 4/0-4/0	

PRODUCT NO.	BATTERY PLATFORM	KIT INCLUDES
SLA-RL758UX	MILWAUKEE	6.6 Ton Latched-Head Crimping Tool (Bare Tool Only)
SLA-RL758U	MILWAUKEE	6.6 Ton Latched-Head Crimping Tool, (2) Milwaukee REDLITHIUM™ Batteries (3.0Ah), AC Charger
SLA-RL758UDC	MILWAUKEE	6.6 Ton Latched-Head Crimping Tool, (2) Milwaukee REDLITHIUM™ Batteries (3.0Ah), DC Charger
SLA-MK758UX	ΜΑΚΙΤΑ	6.6 Ton Latched-Head Crimping Tool (Bare Tool Only)
SLA-MK758U	ΜΑΚΙΤΑ	6.6 Ton Latched-Head Crimping Tool, (2) Makita Batteries (5.0Ah), AC Charger
SLA-MK758UDC	MAKITA	6.6 Ton Latched-Head Crimping Tool, (2) Makita Batteries (5.0Ah), DC Charger

Huskie Tools is not affiliated with, authorized, or endorsed by Milwaukee Electric Tool Corporation. Milwaukee listed batteries and chargers are being re-sold by Huskie Tools. Milwaukee* M18th REDLITHIUMth are registered trademarks of Milwaukee Electric Tool Corporation, Huskie Tools is not affiliated with, authorized, or endorsed by Makita® Corporation, Makita® listed batteries and chargers are being re-sold by Huskie Tools. Makita* and LXT* are registered trademarks of Makita* Corporation.



SL2

RETRACI WITH

TRIGGER

75KV

TOOL WARRANTY

180° HEAD TURN RADIUS

HIIGKI PRO TIP ALWAYS CUT MATERIAL AT MATERIAL AT 90 DEGREES TO THE BLADES FOR BEST RESULTS

П











